

## LTF 104 D FULL HEIGHT TURNSTILE

### Operation

Adjustable manual passage to either direction. Optional: Motorized

### Chassis

1.5 mm thick, AISI 304 quality stainless steel.

Optional: AISI 316 quality. With various color options electrostatic powder coated.

### Rotor and Arms

4 winged 6 arms, AISI 304 quality stainless steel.

Optional: AISI 316 quality. With various color options electrostatic powder coated.

### Functions

Passage information. Ability to set the passage time. Memory mode.

Adjustable audio warning.

### Mechanism

Tempered steel and zinc coating.

Fail-Safe (Free passage during power failure). Optional: Fail lock.

### Emergency Mode

The arms allow free passage when the signal received from fire detection system.

### Operating Voltage

100-230 VAC, 47-60 Hz

### Power Consumption

14W during passages, 24W during stand-by

### Operating Temperature

-20° / +70° Optional: with heater -50°

### Passage Speed

~40 persons / minute.

### Passage Width

47 cm

### Weight

~300 kg

### Security Level

Deterrent.

### Indicators

Standart in both directions.

### Areas of Use

Suitable for indoor and outdoor use.

### Accessories

Heater. Stainless steel reader bracket. Button control unit.

Remote control unit. Coin console. Stainless steel bottom plate.

RS232 / RS485 / LAN communication unit. Adaptor.

